

KP900/KP901-DW

SUPER HEAVY DUAL WHEEL KINGPINLESS

The KP900-DW Series is for the most extreme working conditions. Designed with wheels for the easiest swiveling.


Engineering Data:

- ¾" steel top plate.
- 7" Raceway.
- ½" embossed legs welded inside and out to support base.

Standard Features/Components:

- Powder-coated finish.
- 1¼" axle.
- Lubrication fittings.
- 1½ x 1¼ x 4⅝" hardened spanners.
- Companion Rigid.

Raceway Construction:



KP900-8TD-DW-SL

- Shown with optional SL-4 position swivel lock.

KP900-DW SWIVEL & KP901-DW RIGID SPECIFICATIONS											
WHEEL SPECIFICATIONS				CATALOG NUMBER							
Diameter inches	Width inches	Type	Cap Each lbs	Swivel		Rigid		Approx. Weight lbs	Swivel Radius inches	Height Overall inches	Top Plate inches
				Roller Bearings	Timken Bearings	Roller Bearings	Timken Bearings				
6	8	Paythane	11500	KP900-6UL-DW	KP900-6TL-DW	KP901-6UL-DW	KP901-6TL-DW	81	5¼	9¼	Width by Length: 8½ x 8½
	6	Payductile	18000	KP900-6x3UD-DW	KP900-6x3TD-DW	KP901-6x3UD-DW	KP901-6x3TD-DW	79			
	8	Payductile	18000	KP900-6UD-DW	KP900-6TD-DW	KP901-6UD-DW	KP901-6TD-DW	90			
8	8	Paythane	11500	KP900-8UL-DW	KP900-8TL-DW	KP901-8UL-DW	KP901-8TL-DW	88	6½	10¾	Bolt Hole Spacing: 7 x 7
	6	Payductile	12000	KP900-8x3UD-DW	KP900-8x3TD-DW	KP901-8x3UD-DW	KP901-8x3TD-DW	81			
	8	Payductile	18000	KP900-8UD-DW	KP900-8TD-DW	KP901-8UD-DW	KP901-8TD-DW	112			
10	8	Paythane	11500	KP900-10UL-DW	KP900-10TL-DW	KP901-10UL-DW	KP901-10TL-DW	110	7⅝	13¼	Size of Bolt Holes: 1⅞
	6	Payductile	18000	KP900-10x3UD-DW	KP900-10x3TD-DW	KP901-10x3UD-DW	KP901-10x3TD-DW	89			
	8	Payductile	18000	KP900-10UD-DW	KP900-10TD-DW	KP901-10UD-DW	KP901-10TD-DW	120			
12	8	Paythane	11500	KP900-12UL-DW	KP900-12TL-DW	KP901-12UL-DW	KP901-12TL-DW	130	8¾	15¼	
	8	Payductile	18000	KP900-12UD-DW	KP900-12TD-DW	KP901-12UD-DW	KP901-12TD-DW	140			

- Comes standard with tapered bearing.