

# Payvulc

## VULCANIZED MOLD-ON RUBBER WHEELS

These mold-on rubber wheels are standard with steel centers. A soft rubber tread protects the floor and affords quiet operations. The steel center is fully machined, and is equipped with roller bearings and grease fittings.



**06200-UP**

VULCANIZED MOLD-ON RUBBER WHEELS												
WHEEL		CATALOG NUMBER		Cap. Each lbs.	Approx. Weight lbs.	HUB LENGTH		BORE DIMENSIONS			Used in Caster Series	
Diameter inches	Tread Width inches	Roller Bearings	Bored for, but less Roller Bearings			Without Spanner inches	With Spanner inches	Without Bearing inches	With Bearing inches	Axle Dia. w/spanner inches		Bore Variations inches
4	2	04200-UP	04200-XP	300	2	2 <sup>3</sup> / <sub>16</sub>	2 <sup>5</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	1, 7/8, 5/8	190, 200
5	2	05200-UP	05200-XP	400	3	2 <sup>3</sup> / <sub>16</sub>	2 <sup>5</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	1, 7/8, 5/8	190, 200
6	2	06200-UP	06200-XP	450	4	2 <sup>3</sup> / <sub>16</sub>	2 <sup>5</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	1, 7/8, 5/8	190, 200
8	2	08200-UP	08200-XP	500	6	2 <sup>3</sup> / <sub>16</sub>	2 <sup>5</sup> / <sub>16</sub>	1 <sup>3</sup> / <sub>16</sub>	3/4	1/2	1, 7/8, 5/8	190, 200
10	2 1/2	10250-UP	10250-XP	790	11	2 3/4	2 13/16	1 1/16	1	3/4	1 1/4, 7/8	300

Spanner bushings should be ordered separately. See parts list page 94.

# Pneumatic

## FULL PNEUMATIC WHEELS

Full Pneumatic Wheels act on the same principle as an automobile tire: that is, the tires are air-inflated.\* Accordingly, these wheels are shock-resistant and ideal for delicate and fragile loads.

\*Foam filling available.



**08300-BW**

FULL PNEUMATIC WHEELS												
WHEEL		CATALOG NUMBER		Cap. Each lbs.	Approx. Weight lbs.	HUB LENGTH		BORE DIMENSIONS			Used in Caster Series	
Diameter inches	Tread Width inches	Roller, Ball Bearings				Without Spanner inches	With Spanner inches	Without Bearing inches	With Bearing inches	Axle Dia. w/spanner inches		Bore Variations inches
6	2	06200-BW		260	2 1/2	2 1/2		—	1/2	1/2	—	190, 200
8	2.80-4	08300-BW		320	4 1/2	3 1/4	3 3/8	—	1	3/4	—	400
10	3.50-4	10400-UW		515	8	4 1/4	3 3/8	—	1	3/4	—	400
12	4.00-6	12400-UW		700	12	4 1/4	4 3/8	—	1	3/4	—	400

\*Capacities for Full Pneumatic Wheels are for 50lbs. Tire inflation and operation under 5mph. Spanner bushings should be ordered separately. See parts list page 94.