

# KP800/KP801-DW

## EXTRA HEAVY DUAL WHEEL KINGPINLESS

The KP800 Dual Wheel Series is designed for units up to 48,000 lbs.


**Engineering Data:**

- 5/8" steel top plate.
- 3/8" embossed legs welded inside and out to support base.

**Standard Features/Components:**

- Powder-coated finish.
- 1 1/4" axle.
- 1 1/2 x 1 1/4 x 4 5/8" hardened spanners.
- Lubrication fittings.
- Companion rigid.

**Raceway Construction:**



**KP800-8TL-DW**

- 8" swivel
- Timken bearings
- Paythane polyurethane on cast iron wheel

KP800-DW SWIVEL & KP801-DW RIGID SPECIFICATIONS													
WHEEL SPECIFICATIONS				CATALOG NUMBER									
Diameter inches	Width inches	Type	Cap Each lbs	Swivel		Rigid		Approx. Weight lbs	Swivel Radius inches	Height Overall inches	Top Plate inches		
				Roller Bearings	Timken Bearings	Roller Bearings	Timken Bearings						
6	8	Paythane	11500	KP800-6UL-DW	KP800-6TL-DW	KP801-6UL-DW	KP801-6TL-DW	62	5 1/4	9	Width by Length: 6 1/2 x 7 1/2		
		Payductile	12000	KP800-6UD-DW	KP800-6TD-DW	KP801-6UD-DW	KP801-6TD-DW	68					
8	8	Paythane	11500	KP800-8UL-DW	KP800-8TL-DW	KP801-8UL-DW	KP801-8TL-DW	74	6 1/2	11		Bolt Hole Spacing: 4 1/2 x 6	
		Payductile	12000	KP800-8UD-DW	KP800-8TD-DW	KP801-8UD-DW	KP801-8TD-DW	86					
10	10	Paythane	11500	KP800-10UL-DW	KP800-10TL-DW	KP801-10UL-DW	KP801-10TL-DW	94	7 5/8	13			Size of Bolt Holes: 3/16
		Payductile	12000	KP800-10UD-DW	KP800-10TD-DW	KP801-10UD-DW	KP801-10TD-DW	108					
12	12	Paythane	11500	KP800-12UL-DW	KP800-12TL-DW	KP801-12UL-DW	KP801-12TL-DW	107	8 3/4	15			
		Payductile	12000	KP800-12UD-DW	KP800-12TD-DW	KP801-12UD-DW	KP801-12TD-DW	124					

• Weights shown are for swivels; deduct approximately 15% for rigid casters.